

## Sandblast Stendl Cross Reference Guide

Phone 800-543-1340 Fax 513-771-3327 www.hartcoservice.com

		<b>ANCHOR</b>	3M
Hartco 135 Available in paper liner. 1355-1", 2", 15", 25", 30" For Hand Cutting and CNC Routers.	Regular Grip Adhesive (S)  For use with all types of raw wood, pretreated wood, wood alternatives, brick, glazed tile, Avonite, Corian, and some types of stone.	111 112	507 510
Hartco 310  Available in paper liner 3105-15", 20", 25", 30" - Friction Feed* 3105P-15" & 30" - Gerber Punched 310SP1-30" - 1/2" on center pin fed (special order only)	Regular Grip Adhesive (S) For glass, plexiglass, mirror, foam and other smooth surfaces that can be blasted at a lower PSI to a shallow or medium depth.	128 130	N/A
Hartco 425  Available in paper or plastic liner 4255-15", 20", 25", 30" - Friction Feed* 425SP-15" & 30" - Gerber Punched 425SPI- 30" - ½" on center pin fed (special order only)	Regular Grip Adhesive (S) For all painted wood, raw wood, and wood alternative surfaces, primed foam, glass, plexiglass, cast concrete, tile, Avonite, Corian, and some types of stone. For hand cutting or computer plotters.  High Grip Adhesive (HGS) For industrial applications, as well as all stone, brick, concrete, raw wood, and monument substrates having porous surfaces.	128, 130 T227 Also suitable for: 117, 120, 153, & 157 T226 Also suitable for: 116, 125, 155, & 156	N/A
Hartco 535  Available in paper or plastic liner 5355- 15", 20", 25", 30" - Friction Feed* 5355P- 15" & 30" - Gerber Punched 5355P1- 30" - 12" on center pin fed (special order only)	Regular Grip Adhesive (S) For sandblasting on smooth concrete, glazed brick, polished stone, and other smooth surface substrates that require high blasting pressure.  High Grip Adhesive (HGS) For industrial applications, as well as all stone, brick, concrete, and monument substrates having porous surfaces.	112, 124 123,129,154 158, 192 125	507 510 520 N/A
Hartco 930  Available in plastic liner 930S- 15", 20", 25", 30" - Friction Feed* 930SP1- 30" - 1/2" on center pin fed (special order only)	Regular Grip Adhesive (S) For sandblasting on smooth concrete, glazed brick, polished stone, and other smooth surface substrates that require high blasting pressure. As well as all painted wood, raw wood, and wood alternatives, primed foam, glass, plexiglass, Avonite, and Corian.  High Grip Adhesive (HGS) For industrial applications, as well as all stone, brick, concrete, and monument substrates having porous surfaces.	117 120, 153 157 116 125, 155 156	507 510 520 N/A

<sup>\*</sup> All friction feed products are suitable for cutting by hand as well.